

1. PRODUCT AND COMPANY IDENTIFICATION	
---------------------------------------	--

Product Identifier	
Product Name:	DRIVEN RACING OIL BRAKE & PARTS CLEANER
Product Number:	692100
Recommended Use:	Cleaning agent
Uses Advised Against:	No information available.
Manufacturer/Supplier:	Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, Ohio 43537 USA
Company Phone Number:	800-537-8990 (Business hours)
Website	www.spartanchemical.com
24 Hour Emergency Phone Numbers:	
Medical Emergency/ Information:	888-314-6171
Transportation/Spill/Leak:	CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION	
---------------------------	--

GHS Classification	
Serious Eye Damage/Eye Irritation:	Category 2A
Carcinogenicity:	Category 2
Reproductive Toxicity:	Category 2
Specific Target Organ Toxicity (Single Exposure):	Category 3
Aspiration Toxicity:	Category 1
Flammable Aerosols	

	Category 1	
--	------------	--

Gases Under Pressure		

	Compressed gas	
--	----------------	--

GHS Label Elements	
Signal Word:	Warning
Symbols:	

Hazard Statements:	Causes serious eye irritation Suspected of causing cancer Suspected of damaging fertility or the unborn child May cause respiratory irritation. May cause drowsiness or dizziness May be fatal if swallowed and enters airways
Physical Hazards:	Extremely flammable aerosol.
Physical Hazards:	Contains gas under pressure; may explode if heated

Precautionary Statements:	
Prevention:	Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wear eye / face protection Wear protective gloves Wash hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Response:	If exposed or concerned: Get medical attention.
-Eyes	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
-Inhalation:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell
-Ingestion:	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting.
-Specific Treatment:	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Storage:	Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C) Store in a well-ventilated place
Disposal:	Dispose of contents and container in accordance with local, state and federal regulations.
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	<ul style="list-style-type: none"> • May be harmful if swallowed. • May cause skin irritation. • Keep out of reach of children.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
acetone	67-64-1	60-100
carbon dioxide	124-38-9	5-10
Heptane	142-82-5	3-7
xylene	1330-20-7	1-5
ethylbenzene	100-41-4	0.1-1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
-Skin Contact:	Wash with soap and water. If skin irritation occurs: Get medical attention.
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.
-Ingestion:	IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Do NOT induce vomiting.
Note to Physicians:	Potential for aspiration if swallowed.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Alcohol resistant foam, Water spray (fog), Dry chemical
Specific Hazards Arising from the Chemical:	Extremely flammable aerosol. Exposure to high temperature may cause containers to burst. Bursting aerosol containers may be propelled from fire at high speed.
Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.
---	---

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Remove all sources of ignition.
Environmental Precautions:	Do not rinse spill onto the ground, into storm sewers or bodies of water.
Methods for Clean-Up:	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling:	Handle in accordance with good industrial hygiene and safety practice. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash thoroughly after handling.
Storage Conditions:	NFPA 30B Level 3 Aerosol. Do not store in direct sunlight or above 122 F° / 50 C°. Exposure to high temperature may cause containers to burst. Keep out of the reach of children.
Incompatible Materials:	Strong acids. Strong oxidizing agents. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Engineering Controls:	Provide good general ventilation. If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.
Personal Protective Equipment	
Eye/Face Protection:	Wear splash goggles.
Skin and Body Protection:	Wear rubber or other chemical-resistant gloves.
Respiratory Protection:	Not required with expected use. If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.
General Hygiene Considerations:	Wash hands and any exposed skin thoroughly after handling. See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

--	--

Appearance/Physical State:	Aerosol
-----------------------------------	---------

Color:	Clear
---------------	-------

Odor:	solvent
--------------	---------

pH:	Not applicable
------------	----------------

Melting Point / Freezing Point:	No information available.
--	---------------------------

Boiling Point / Boiling Range:	61 °C / 142 °F
---------------------------------------	----------------

Flash Point:	< -18 °C / < 0 °F (Propellant-estimated)
---------------------	--

Evaporation Rate:	< 1.0 (Butyl acetate = 1)
--------------------------	---------------------------

Flammability (solid, gas)	No information available.
----------------------------------	---------------------------

Upper Flammability Limit:	No information available.
----------------------------------	---------------------------

Lower Flammability Limit:	No information available.
----------------------------------	---------------------------

Vapor Pressure:	No information available.
------------------------	---------------------------

Vapor Density:	No information available.
-----------------------	---------------------------

Specific Gravity:	0.726 (Product without propellant)
--------------------------	------------------------------------

Solubility(ies):	Insoluble in water
-------------------------	--------------------

Partition Coefficient:	No information available.
-------------------------------	---------------------------

Autoignition Temperature:	No information available.
----------------------------------	---------------------------

Decomposition Temperature:	No information available.
-----------------------------------	---------------------------

Viscosity:	No information available.
-------------------	---------------------------

10. STABILITY AND REACTIVITY

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical Stability:	Stable under normal conditions.
Possibility of Hazardous Reactions:	Not expected to occur with normal handling and storage.
Conditions to Avoid:	Extremes of temperature and direct sunlight.
Incompatible Materials:	Strong acids. Strong oxidizing agents. Chlorinated compounds.
Hazardous Decomposition Products:	May include carbon monoxide, carbon dioxide (CO ₂) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Eyes, Skin, Ingestion, Inhalation.
Symptoms of Exposure:	
-Eye Contact:	Pain, redness, swelling of the conjunctiva and blurred vision.
-Skin Contact:	Drying of the skin.
-Inhalation:	Nasal discomfort and coughing. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
-Ingestion:	Pain, nausea, vomiting and diarrhea. Potential for aspiration if swallowed.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: Central nervous system. -Eyes. Respiratory System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral):	6695 mg/kg
ATEmix (dermal):	30319 mg/kg
ATEmix (inhalation-dust/mist):	66 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
acetone 67-64-1	= 5800 mg/kg (Rat)	Not Available	Not Available
Heptane 142-82-5	Not Available	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h
ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ethylbenzene 100-41-4	Not Listed	Group 2B	Not Listed	Not Listed

IARC (International Agency for Research on Cancer): Group 2B - Possibly Carcinogenic to Humans

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
acetone 67-64-1	Not Available	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Heptane 142-82-5	Not Available	375.0: 96 h Cichlid fish mg/L LC50	Not Available	10: 24 h Daphnia magna mg/L EC50
xylene 1330-20-7	Not Available	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	Not Available	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/ L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/ L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	Not Available	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
--------------------------	--	--	---------------	--

Persistence and Degradability:	No information available.
Bioaccumulation:	No information available.
Other Adverse Effects:	No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:	Dispose of in accordance with federal, state and local regulations.
Contaminated Packaging:	Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with federal, state and local regulations.
US EPA Waste Number:	D001, U002, U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
acetone 67-64-1		Included in waste stream: F039		U002
xylene 1330-20-7		Included in waste stream: F039		U239
ethylbenzene 100-41-4		Included in waste stream: F039		

14. TRANSPORT INFORMATION

DOT:	Regulated
UN/ID No:	UN1950
Proper Shipping Name:	Aerosols
Hazard Class:	2.1
Special Provisions:	This product meets the exception requirements of section 49 CFR 173.306 as a limited quantity and may be shipped as a limited quantity. Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)
All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313
This product contains the following listed substances:
xylene
format format CAS No 1330-20-7 format format 1.0
ethylbenzene
format format CAS No 100-41-4 format format 0.1

SARA 311/312 Hazard Categories	
Acute Health Hazard:	Yes
Chronic Health Hazard:	Yes
Fire Hazard:	Yes
Sudden release of pressure hazard:	No

Reactive Hazard:	No
-------------------------	----

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
ethylbenzene - 100-41-4	Carcinogen
toluene - 108-88-3	Developmental Female Reproductive

WARNING: This product contains a chemical known to the State of California to cause cancer.

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

--

16. OTHER INFORMATION

--

NFPA			
-------------	--	--	--

	Health Hazards: 2		
--	--------------------------	--	--

	Flammability: 3		
--	------------------------	--	--

	Instability: 0		
--	-----------------------	--	--

	Special: N/A		
--	---------------------	--	--

--

HMIS			
-------------	--	--	--

	Health Hazards: 2*		
--	---------------------------	--	--

	Flammability: 4		
--	------------------------	--	--

	Physical Hazards: 2		
--	----------------------------	--	--

--	--	--	--

Revision Date:	10-Jun-2015
Reasons for Revision:	No information available.

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

--

End of Safety Data Sheet